

- 1/4", 1/2", 1" Thicknesses
- Washable for Repeated Use
- Withstands Wide Temperature Extremes

Applications

Widely used as a permanent washable filter in place of metal filters or disposable panel filters in HVAC equipment, including:

- Room Airconditioners
- Fan Coil Units
- Unit Ventilators
- Air Handling Units
- Built Up Filter Banks

Washable for Repeated Use

The media can be cleaned for re-use by vacuuming, flushing, washing in warm water and detergents, even steaming.

Suitable for Difficult Operating Conditions

Foam media can withstand wide temperature extremes - from -50°F to +250°F. It can be sterilized in boiling water or steam. The chemical make up of foam media is not adversely affected by water, soap, detergents, oils, solvents or greases at normal temperatures.

Foam Filter Media

Permanent Washable Filter Roll Media



Foam filter media is made with 30 pores per inch. It is available in pre-cut or bulk rolls.

Performance Data	1/4"	1/2"	1"
Initial Resistance (In. W.G) @300 FPM	.05"	.12"	.16"
Arrestance	55%	60%	65%
Recommended Final Resistance (In. W.G)	.50"	.50"	.50"



www.clcair.com







ATI-FOAM-0613

Distributed by:



© 2013 CLARCOR Air Filtration Products.

CLARCOR Air Filtration Products has a policy of continuous product research and development and reserves the right to change design and specifications without notice. Terms and Conditions of Sale can be accessed at www.clcair.com